


Manager IQ Easy  
 1030000000 - 24V DC powered  
 1030000010 - 100-240V AC powered


Sub-D connector  
 male 25 pole  
 3900236025



Power cord IEC-C13  
 2 m, with lock  
 9146340700

24V power connector  
 for Ø4 - 6,5 mm cables  
 9370000205

Extension IQ Easy  
 1030000100 - 24V DC powered  
 10300000110 - 100-240V AC powered



Connector IQ M12 male straight  
 5 pole (screw connections)  
 7519020352 - Ø4-6 mm cables  
 7519020353 - Ø6-8 mm cables

Status Module  
 4530000300



Cord device M12 female angled 5 pole  
 7519020375 - 5 m, unshielded  
 7519020376 - 10 m, unshielded



Cord device M12 female straight 5 pole  
 7519020365 - 5 m, unshielded  
 7519020366 - 10 m, unshielded

Connector device M12 female angled  
 5 pole (screw connections)  
 7519020355 - Ø4-6 mm cables  
 7519020356 - Ø6-8 mm cables

Connector device M12 female straight  
 5 pole (screw connections)  
 7519020350 - Ø4-6 mm cables  
 7519020351 - Ø6-8 mm cables

Cord device M12 fem.-male straight 5 pole  
 7519020390 - 2m, unshielded  
 7519020391 - 5m, unshielded  
 7519020392 - 10m, unshielded  
 7519020393 - 20m, unshielded  
 7519020394 - 25m, unshielded

Cord IQ interconnection M8  
 female-male straight 3 pole  
 7519020291 - 5m  
 7519020292 - 10m  
 7519020294 - 25m



Protective hose ATEX  
 9380531320 per m  
 Hose clip ATEX  
 9250101013 needed 4 pieces/m hose  
 Fitting ATEX  
 9370521017

ATEX ZONE

NON-ATEX ZONE

**Ex Certified Product**  
 No modifications permitted without the approval of the "authorised person"

Remark:

- The Status Module Performax (IQ) Easy EX has a connection for one bar

 An ITW Company www.simco-ion.nl Tel: +31 (0)573 288333	Name: Performax IQ Easy EX (Speed) system overview				Drawn: RJ	Part no.: —
	CAD generated NOT updated	Dimensions in mm	Date: 7-2-2017	A3 M: 1:1	ECN-	Check: -